



# KANOMAX FMT

A Kanomax Company

## ***Handheld Condensation Particle Counter Model 3800***

### **Handheld particle detection down to 15 nm!**

In Approaches to Safe Nanotechnology, NIOSH recommends direct-reading instruments and filter sampling with lab analysis to obtain particle number, size, and shape, degree of agglomeration, and mass concentration of elemental constituents in nanoparticles. Direct reading instruments include both optical particle counters and condensation particle counters such as the Kanomax 3800.

### ***Applications***

- Indoor Air Quality Investigation
- Occupational Health Control
- Gasket Leakage Testing Engine
- Exhaust Testing Filter Testing
- Aerosol Research



Checking worker exposure to airborne contaminants




Leakage testing



Engine exhaust testing

### ***Features & Benefits***

- Particle size range : 15 to 1,000 nm
- Measuring range : 0 to 100,000 particles/cm<sup>3</sup>
- Sampling airflow : 0.7 L/min
- Data logging up to 10,000 measurements
- USB interface for data transfer
- Handy and Light weight
- Weight : 1.5 kg
- Power supply : 6 × AA batteries or AC adapter



Windows 7 compatible Software included

## Handheld Condensation Particle Counter Model 3800 Specifications

<b>Measuring Particle Size</b>		15 ~ 1,000 nm
<b>Concentration Range</b>		0 ~ 100,000 particles/cm <sup>3</sup> (coincidence error < 5 %)
<b>Counting Efficiency</b>		50 nm : 100 ± 20 % (15 nm : More than 50 %)
<b>Zero Count Level</b>		Less than 1 particle/cm <sup>3</sup>
<b>Flow Rate</b>		Aerosol Flow : 0.1 L/min Total Flow : 0.7 L/min
<b>Alcohol Supply</b>	<b>Type</b>	100 % Reagent Grade Isopropyl Alcohol
	<b>Hours Per Fill</b>	5 hours at 71 °F (21 °C)
<b>Absolute Pressure Sensor</b>		150 ~ 1,150 hPa
<b>Mode of Measurements</b>		Repeat / Program / Counter
<b>Display</b>		Built-in LCD
<b>Interface</b>		USB, Printer Output Port
<b>Data Storage</b>		10,000 samples
<b>Power Supply</b>	<b>Type</b>	AA Alkaline or Ni-MH Battery / AC Adapter (AC 100 ~ 240 V)
	<b>Operating Time</b>	5 hours (by Alkaline Battery) / 8 hours (by Ni-MH Battery)
<b>Operating Environment</b>		Ambient Temperature Range : 50 ~ 95 °F (10 ~ 35 °C)
<b>Dimensions (W,H,D)</b>		12 cm × 28 cm × 13 cm (w/o battery)
<b>Weight</b>		1.5 kg
<b>Warranty</b>		1 year
<b>Standard Accessories</b>		Operation Manual, Carrying Case, AC Adapter, Zero Filter PC Community Cable, Data Processing Software, and Calibration Certificate
<b>Optional Accessories</b>		Thermal Printer, Printer Cable, Sampling Probe

Specifications subject to change without notice.



# KANOMAX FMT

A Kanomax Company

## KANOMAX FMT, INC.

4101 Hoffman Rd.  
White Bear Lake, MN 55110 USA  
TEL: +1.651.762.7762  
ContactUs@KanomaxFMT.com  
www.KanomaxFMT.com

Distributed by:

香港商衛利精控科技有限公司台灣分公司  
744002台南市新市區中山路224號3樓  
Tel: (06)589-5892  
Fax: (06)589-1683  
E-mail: twsales@winifred-hk.com