

Specifications		
Product	Multi-Channel Anemomaster PRO Main Unit	
Model	Model 1590-00	
Display, Operation	7-inch color LCD with touch panel	
Communication Function	Data	USB Type-A: For USB memory
	Remote measurement	Modbus (Ethernet, USB Serial)
	Between units	RS485 (Standard cable)
Recording Media	Medium	Built-in memory
	Format	CSV format
	Recording capacity	8GB (One hub unit can measure 1000 sampling times, about 24500 times.)
External Trigger Input	Pin jack terminal Φ2.5 audio jack (Edge detection at start)	
Language	Japanese, English, Chinese	
Power Supply	DC12 to 24V (Select either one of 3 options below) 1) Connection with other unit, 2) AC adaptor (90W or 160W), 3) DC power cable	
Power consumption	10W	
Size	W220 mm × D130 mm × H40 mm	
Weight	0.6 kg	
Standard Accessories	AC Adapter (90W), Software (CD), Operation manual, USB cable, Stylus pen, Rubber cap	
Warranty	1 year	

Product	HUB Unit	
Model	Model 1591-00	
Number of channels	12ch	
Communication Function	Between Probes	Serial communication (standard cable)
	Between Units	Serial communication (standard cable, connector)
Power Supply	DC12 ~ 24V Power supply method conforms to the main unit	
Power consumption	to the main unit	
Size	Up to 50W	
Weight	W220mm × D130mm × H40mm	
Standard Accessories	0.5kg Setup guide, Connecting clips (2pcs)	
Warranty	1 Year	

Common specifications for unit		
Operating Environment	5~40℃、0~85%RH(No Condensation)	
Storage Environment	-10~60℃、0~90%RH (No Condensation)	

Product	Analog Unit	
Model	Model 1592-00	
Number of channels	12ch	
Communication Function	Between units	Serial communication (standard cable, connector)
Analog Output	Voltage output	Range 0 ~ 5V
	Current output	Output resistance 1kΩ
		Range 4 ~ 20mA
		Load resistance 250Ω
	DC12 ~ 24V Power supply method conforms to the main unit	
	10W	
Size	W220mm × D130mm × H40mm	
Weight	0.5kg	
Standard Accessories	Setup guide, Connecting clips (2pcs), Rubber cap (2pcs), Terminal block (3pcs)	
Warranty	1 year	

Specification of Probe																
Model Number	Measurement Target	Directivity	Air Velocity			Wind Temperature		Humidity		Operating Temperature	Temperature compensation sensor					
			Measurement Range	Measurement Accuracy	Responsivity	Measurement Range	Measurement Accuracy	Measurement Range	Measurement Accuracy							
0972-00	Wind Speed	Yes	0.01~50.0m/s	The larger of ± 2% or ± 0.02 m/s of the displayed value	1 second	—	—	—	—	0-100℃	± 5% of displayed value at 0-100 ℃					
0973-00			0.01~25.0m/s													
0975-00																
0975-09		0.01~50.0m/s	3 second	—	—					—	—	—	0-120℃	± 5% of displayed value at 0-120 ℃		
0975-10																
0976-03		0.01~30.0m/s													The larger of ± 3% or ± 0.02 m / s of the displayed value	0-100℃
0976-04																
0976-07																
0976-13													No	0.01~30.0m/s		
0976-14																
0976-17																
0976-05	Air Velocity and Temperature	0.01~25.0m/s				The larger of ± 3% or ± 0.02 m/s of the displayed value	0-120℃	± 5% of displayed value at 0-120 ℃								
0976-15																
0975-21			The larger of ± 2% or ± 0.02 m/s of the displayed value	0~100℃	± 0.5%				5~95%RH	5~80%RH: 3%RH 80~90%RH: 5%RH	0-100℃	± 5% of displayed value at 0-100 ℃				
0975-31	Air Velocity, Temperature and Humidity	0~60℃														

Responsivity: Indicated value gets 0.9m/s or more than 0.9m/s to "air velocity 1m/s" or the certain temperature condition



### KANOMAX USA,INC.

219 US Hwy 206, Andover NJ 07821 USA  
TEL : +1 973-786-6386  
E-mail : sales@kanomax.com  
URL : www.kanomax-usa.com

●Distributed by :

香港商衛利精控科技有限公司台灣分公司  
744002台南市新市區中山路224號3樓  
Tel: (06)589-5892  
Fax: (06)589-1683  
E-mail: twsales@winifred-hk.com

E1590-2E



# Multi-Channel Anemomaster PRO

## MODEL 1590



Accurate simultaneous multi-channel measurement from large to narrow spaces


- 15 types of compatible probes for various applications
- The smallest class probe in the industry
- High heat resistance enables precise measurement even in tough environments.
- Large-scale system configuration with max.144 ch available
- Measurement in large-scale space is easy
- High portability of the main body makes it easy to use in vehicles.
- Improved probe response and accuracy, micro air velocity limit of 0.01 m/s



Flexible system construction that allows you to select the number of channels, measurement items, and sensor shape according to your purpose.

The accuracy and responsiveness of the entire velocity range, including the breeze speed range, which are highest level in the world. Multipoint measurement on up to 144 channels is realized with the industry's smallest level miniature probe, high heat resistance, and temperature measurement. Due to the high portability of the main unit and the enhanced interface, we pursued simultaneous measurement of multiple points in a shorter time, more easily, and ease of use.

System configuration Example




Supports analog output


By connecting an optional analog unit, it is possible to record the measurement results to your data logger. Each analog unit has 12 channels, and the electric current or voltage can be selected for each channel. A maximum of 12 units and 144 channels can be added with one main unit, making it ideal for data collection using a data logger.

Software

This product comes with a Windows version of the measurement software. Simultaneous measurement of all channels of air velocity, temperature and humidity, and real-time graph display. The measurement data is saved in text format and can be easily imported into table measurement software such as Excel. There are two types of communication interfaces, USB and LAN. There are two ways to configure the settings: by operating the touch panel on the main unit, or remotely from a PC via USB or LAN.



Application Example



Air velocity range of compatibility probes to meet a many different type of customer needs

15 Types of Probes Are Available

Model 0972-00



Model 0973-00



Model 0975-00




Model 0975-09 / 21



Model 0975-10



Model 0976-03 / 13




Model 0976-04 / 14




Model 0975-31



Model 0976-05 / 15 0976-07 / 17



Probe Dimensions



Available Accessories

AC adapter

Model 1580-10  
Output power : 90W  
Input : AC100-240V  
50/60Hz, 1.5A

Standard cable

Model	Length
1580-30	0.5m
1580-31	2m
1580-32	5m
1580-33	10m
1580-34	20m
1580-35	40m

DC power connection cable

Model 1580-37  
Length : 2m  
Supply voltage : 12 ~ 24V  
Power capacity : Maximum 6.25A  
(Maximum about 150W)

Probe fixing jig

Model 1580-90  
Compatible probe : 0976-03/04 0976-13/14  
Upper-temperature limit : 150°C  
Quantity : 20 pairs / 1 pack

Double-coated tape for 0976

Model 1580-92  
Compatible probe : 0976-05/07 0976-15/17  
Size : φ5.5×t0.3mm  
Upper-temperature limit : 120°C  
Quantity : 200 pairs / 1 pack

Probe fixing example

Example of probe with the double-sided tape